



UNI-MAG™ MAGNET



INTRODUCTION

UNI-MAG™ is a heavy duty wellbore clean-up magnet suitable for all downhole conditions and with robust, high performance features.

Run separately or as part of a comprehensive wellbore clean-up, the UNI-MAG™ is designed to capture ferrous metal debris in the wellbore.

The magnetic inserts are arranged along ribs to create a debris trap, by encouraging fluid flow between the ribs, maximizing contact time with the magnets. The magnetic inserts are securely held in tongued grooves and cannot come loose downhole.

Non-rotating sleeves are mounted on alloy bronze bearings, featuring both axial and radial elements, to allow extended rotation in harsh environments, preventing tool and casing wear.

FEATURES

- 8 rows of magnets arranged to trap and retain debris in the wellbore
- Centralizers provide centralization and rotation of the tool body without casing wear
- Non rotating design with high performance alloy bronze bearings compatible with high temperature and chemical applications
- Available with all API and premium drill pipe connections

BENEFITS

- A properly executed wellbore clean-up mitigates risk during completion operations and the productivity of the well.
- Prevent metal debris related completion failure
- Remove swarf, perforation debris and other metal debris from the wellbore

Reactive Downhole Tools Ltd.
Balgownie Lodge | Aberdeen |
United Kingdom | AB22 8GW

REACTIVETOOLS.COM



APPLICATIONS

- Pre-completion wellbore clean-up
- Workovers and sidetracking
- Abandonment
- Drilling / milling cement plugs



UNI-MAG™ MAGNET



OPERATIONAL

The UNI-MAG™ can be run alone or as part of a comprehensive wellbore clean-up BHA. It is typically run in a BHA above a casing scraper and brushes as it complements the hard scraping/brushing action to remove rust-scale from the wellbore.

The UNI-MAG™ is centered in the casing by two non-rotating Centralizers. These guide and centralize the tool, which allows extended rotation without wearing the casing. While running in the hole or circulating, the well fluid passes along channels between the magnetized ribs capturing ferrous debris. The ribs also prevent debris from being knocked off while circulating or tripping.

The robust tool design, non-rotating centralizers and large debris capacity allow milling of packers, or clean-up of casing windows, to be simple and efficient.



TECHNICAL SPECIFICATIONS*

Nominal OD (in.)	Max. Weight (ppf.)	Connection	Centralizer OD (in.)	Magnet Debris Capacity (lbs.)	ID (in.)	Length (in.)	Tensile Yield† (lbs.)	Torsional Yield† (ft.lbs.)	Max Slack-Off (lbs.)	Burst/Collapse (psi.)	Max Rotation (rpm.)
7.000	29.0 38.0	NC 38	6.054 5.790	58	1.875	204	523,200	28,600	10,000	>10,000	120
9.625	43.5 53.5	NC 50	8.594 8.374	115	3.00	200	927,000	59,800	20,000		

*Specifications are for marketing purposes only and may be subject to change. No warranties implied.